



BOOM LIFT TIRES:



HF-3

R-4

PATTERN FEATURES:

- Directional R-4 tread
- Wider tire lugs and flat profile design give maximum surface contact
- Heavier ply construction, special rubber compound blend, reinforced tire bead and rim guard design
- R-4 tires offer a shorter, stiff side wall and reduced interior cavity space

SIZE	PR	PATTERN NO.	TYPE	T.D.(mm)	STD.RIM	MAX LOAD (kg)	INFLATION (kPa)	S.W. (mm)	O.D. (mm)
445/50D710	24	R-4	TL	25	W15	12200	1000	445	1189
445/50D710	20	R-4	TL	25	W15	7740	790	445	1189
445/50D710	18	R-4	TL	25	W15	7300	690	445	1189
385/45-28	18	R-4	TL	25	13.00	8500	1000	376	1082
18-625	16	R-4	TL	25	15.00	6900	690	450	1033
15-625	16	R-4	TL	25	13.00	5580	690	385	1018
355/55D625	14	R-4	TL	22.5	11.75	3450	520	360	936
33X12D610	12	R-4	TL	20	10	3880	550	305	838
445/65-22.5	18	R-4	TL	32	13.00	9000	800	445	1180
385/65D22.5	18	R-4	TL	25	11.75	6900	690	389	1095
39X15-22.5	16	R-4	TL	25	13.00	5580	690	385	1018
315/55D20	12	R-4	TL	19	11	4000	560	319	848
385/65D19.5	16	R-4	TL	25	11.75	4935	690	397	994
385/65D19.5	14	R-4	TL	25	11.75	4625	590	397	994
240/55D17.5	12	R-4	TL	10	6.75	2800	735	230	725
14-17.5	14	R-4	TL	20	10.5	3875	520	348	913
33X15.5-16.5	14	R-4	TL	20	12	3980	490	394	838
26X12D380	8	HF-3	TL	16	10	1550	380	309	670