



Profile L

Profile CA

Size mm D/b-d	Size Inch Dxbxd	Tread		Standard	EC+	Load capacity (kg) up to km/h						Mass Standard kg	
		L	CA			Forklifttruck				Trailer			
						10 Load wheel	16 Steer wheel	16 Load wheel	10 Steer wheel	6	10		16
140/115- 80		●				520	430	465	390		450	370	3,4
152/ 50- 84		●				230	190	205	170	275	180	165	1,3
152/ 60- 84		●				290	240	260	215	340	225	205	1,6
152/ 75- 84		●				385	315	345	285	460	300	275	2,1
152/ 84- 84		●				440	365	390	330	525	345	315	2,2
155/100- 90		●				495	405	440	370		390	355	3,3
216/102-101,6	8 1/2x4 x4	●				700	575	625	525		550	500	5,9
178/ 50-110		●				260	215	230	195	310	205	185	1,7
178/ 75-110		●				435	355	385	325	515	340	310	2,6
229/127-127	9 x5 x5	●				960	790	855	715		750	680	7
254/127-127	10 x5 x5	●				1060	870	950	795		830	755	7,7
267/127-127	10 1/2x5 x5	●	●			1100	900	980	825		860	780	7,9
267/152-127	10 1/2x6 x5	●				1400	1150	1245	1050		1100	1000	11
250/ 75-140		●				560	460	500	420	670	440	400	4,6
250/130-140		●				1065	875	950	800		835	760	8
254/ 90-145		●	▲			735	605	655	550	875	575	525	5,4
250/ 90-150		●				730	600	650	545	870	570	520	5,3
250/ 60-157		●				415	340	370	310	490	325	295	3,2
254/127-158	10 x5 x6 3/16	●				1030	840	915	770	1215	805	730	8,2
254/102-158,8	10 x4 x6 1/4	●				785	645	700	590		615	560	6,4
254/127-158,8	10 x5 x6 1/4	●				1030	840	915	770	1215	805	730	7,8
254/152-158,8	10 x6 x6 1/4	●				1270	1040	1135	950	1515	1000	910	9
230/ 50-160		●				315	255	280	230	375	245	225	2,3
230/ 75-160		●				530	435	470	395	625	410	375	3,7
265/160-160		●				1420	1165	1265	1065		1115	1015	11
260/102-160,5		●				800	660	715	600		630	575	6,8
254/102-165,1	10 x4 x6 1/2	●				780	640	695	585		610	555	6,6
254/127-165,1	10 x5 x6 1/2	●				1015	835	905	760		795	725	7,7
267/127-165,1	10 1/2x5 x6 1/2	●	●			1070	880	960	810		845	770	9
267/152-165,1	10 1/2x6 x6 1/2	●				1340	1100	1190	1000		1045	950	11
267/178-165,1	10 1/2x7 x6 1/2	●				1600	1315	1430	1200		1260	1140	13
250/ 80-170		●				620	510	550	460	735	490	445	4,6
250/ 90-170		●				720	590	640	535	850	560	510	5,2
250/105-170		●				780	640	695	580		610	555	6,3
270/105-170		●				955	775	850	715		750	680	6,9
265/ 85-190		●	●			690	570	620	515	825	540	495	5,5
300/ 80-200		●				710	585	635	530	850	560	510	6
300/110-200		●				985	805	880	735		775	705	9,2
300/ 90-202		●				835	685	745	625	995	655	600	6,9
300/ 90-203		●				835	685	745	625	995	655	600	6,9
310/126-203		●				1200	990	1070	900		940	855	11
310/152-203		●				1505	1240	1345	1130		1180	1075	13
330/ 89-203,2	13 x3 1/2x8	●	●			865	710	775	650	1030	680	615	8
305/102-203,2	12 x4 x8	●	●			905	740	810	680		710	645	9,2
305/114-203,2	12 x4 1/2x8	●	●			1040	855	933	780		820	745	9,6
330/114-203,2	13 x4 1/2x8	●	●			1120	920	100	840		880	800	10
343/114-203,2	13 1/2x4 1/2x8	●	●			1150	940	1025	860		900	820	11
356/114-203,2	14 x4 1/2x8	●	●			1170	960	1045	875		910	830	12
305/127-203,2	12 x5 x8	●	●			1190	980	1065	890		935	850	10
330/127-203,2	13 x5 x8	●	●			1290	1060	1150	965		1010	920	12
356/127-203,2	14 x5 x8	●	●			1360	1120	1215	1020		1070	970	13
343/140-203,2	13 1/2x5 1/2x8	●	●			1510	1240	1345	1130		1190	1080	13,5
300/100-206		●				870	710	775	650		680	620	8,1
280/ 75-220		●				595	490	530	445	710	465	425	5,5
285/ 75-220		●				610	505	550	460	730	480	440	5,6
310/120-220		●				1100	905	985	830		865	790	10,5
300/ 60-230		●				485	400	430	360	575	380	345	3,5
312/ 80-235		●				730	600	650	545	865	570	520	6,3
344/ 90-235		●				925	760	825	690	1090	720	655	8
300/ 75-240		●				625	515	560	465	740	490	445	5,3

Size mm D/b-d	Size Inch Dxbxd	Tread		Standard	EC+	Load capacity (kg) up to km/h							Mass Standard kg
		L	CA			Forklifttruck				Trailer			
						10 Load wheel	16 Steer wheel	10 Load wheel	16 Steer wheel	6	10	16	
340/ 80-240		●				780	645	695	580	925	610	555	6,2
356/127-254	14 x5 x10	●				1335	1100	1200	1000		1050	950	12,5
394/127-254	15 1/2x5 x10	●	●			1470	1210	1315	1100		1155	1050	15
394/152-254	15 1/2x6 x10	●	●			1870	1530	1665	1400		1460	1330	18
350/ 60-255		●				530	440	475	395	625	410	375	4,5
406/114-266,7	16 x4 1/2x10 1/2		●			1300	1070	1160	975		1020	930	16
406/127-266,7	16 x5 x10 1/2	●	●			1510	1240	1345	1130		1190	1080	16
406/152-266,7	16 x6 x10 1/2	●	●			1910	1570	1710	1435		1495	1360	19
406/178-266,7	16 x7 x10 1/2		●			2325	1910	2070	1740		1825	1660	21
360/ 60-270		●				550	450	490	410	650	430	395	5,5
360/ 85-270		●				890	730	795	665	1060	700	635	7,4
350/ 90-280		●				895	740	800	665	1065	700	640	7
385/ 90-285		●				1005	830	895	750	1195	790	720	9
381/108-285		●				1150	945	1025	860		900	820	12
381/127-285,8	15 x5 x11 1/4	●				1390	1140	1240	1040		1090	990	14
413/127-285,8	16 1/4x5 x11 1/4	●	●			1530	1250	1360	1145		1200	1090	16
381/152-285,8	15 x6 x11 1/4	●	●			1715	1410	1530	1285		1345	1225	17
413/152-285,8	16 1/4x6 x11 1/4	●	●			1920	1580	1715	1440		1505	1370	19
380/160-285,8		●				1810	1490	1615	1355		1420	1295	19
381/178-285,8	15 x7 x11 1/4	●				2055	1690	1835	1540		1615	1470	20
413/178-285,8	16 1/4x7 x11 1/4		●			2325	1900	2060	1735		1815	1650	23
381/203-285,8	15 x8 x11 1/4	●				2385	1960	2130	1790		1875	1700	23
450/120-300		●				1650	1355	1475	12356		1295	1180	17,5
460/135-300		●				1790	1470	1600	1340		1405	1280	17
415/ 75-305		●				820	670	730	610	975	640	585	9
415/ 90-305		●				1060	875	945	790	1260	830	760	11
415/100-305		●				1115	915	1000	835		865	795	12
405/130-305		●				1510	1240	1350	1135		1190	1080	16
425/150-305		●				1910	1570	1700	1435		1500	1365	20
405/260-305		●				3325	2730	2970	2495		2610	2375	12,5
450/300-305		●				4640	3810	4145	3480		3650	3320	45
410/ 60-308		●				585	485	510	420	665	440	400	6,2
410/ 80-308		●				895	735	800	665	1065	700	640	8,2
410/ 90-308		●	▲			1060	870	945	790	1260	830	755	9
432/102-308	17 x4 x12 1/8		●			1170	960	1050	875		915	830	13
410/115-308		●				1315	1080	1175	985		1035	940	13
432/127-308	17 x5 x12 1/8	●	●			1570	1290	1400	1180		1230	1120	18
457/127-308	18 x5 x12 1/8	●	●			1640	1350	1470	1230		1285	1170	19
432/152-308	17 x6 x12 1/8	●	●			1980	1630	1770	1485		1550	1410	21
457/152-308	18 x6 x12 1/8	●	●			2100	1720	1870	1575		1650	1500	23
408/160-308		●				1940	1590	1730	1455		1525	1385	20
432/178-308	17 x7 x12 1/8	●	●			2390	1965	2135	1790		1880	1710	24
457/178-308	18 x7 x12 1/8	●	●			2550	2100	2280	1910		2000	1820	27
457/203-308	18 x8 x12 1/8	●	●			3000	2475	2680	2250		2365	2150	30
457/229-308	18 x9 x12 1/8	●	●			3450	2850	3090	2600		2720	2475	32
450/120-316,4		●				1510	1240	1350	1130		1185	1080	17
457/203-355,6	18 x8 x14	●				2780	2285	2480	2085		2185	1985	28
457/229-355,6	18 x9 x14	●				3180	2610	2840	2385		2495	2270	31
450/125-356		●				1540	1265	1375	1155		1210	1100	16
530/ 90-370		●				1175	960	1050	880	1400	925	835	14
530/100-370		●				1275	1050	1140	955		1000	910	15
520/120-370		●				1675	1375	1500	1260		1320	1200	18
500/140-370		●				2000	1640	1785	1500		1570	1430	21
550/150-370		●				2350	1930	2100	1760		1845	1680	29
550/160-377		●				2360	1940	2105	1770		1855	1685	29
533/127-381	21 x5 x15		●			1840	1510	1640	1385		1450	1320	22
533/152-381	21 x6 x15	●	●			2350	1930	2100	1765		1845	1680	28
533/178-381	21 x7 x15	●	●			2875	2350	2560	2150		2255	2050	33
533/203-381	21 x8 x15	●	●			3375	2775	3025	2540		2665	2425	36
533/229-381	21 x9 x15	●	●			3900	3200	3475	2920		3050	2775	40
500/ 90-406,4		●				1220	1005	1090	910		955	870	12
585/ 90-406,4			▲			1180	970	1050	880		925	840	16
500/127-406,4		●				1685	1385	1505	1265		1325	1205	20
508/127-406,4	20 x5 x16	●	●			1740	1430	1560	1310		1375	1250	20
510/127-406,4			▲			1740	1430	1560	1310		1375	1250	20

Size mm D/b-d	Size Inch Dxbxd	Tread		Standard	EC+	Load capacity (kg) up to km/h						Mass Standard kg	
		L	CA			Forklifttruck				Trailer			
						10 Load wheel	10 Steer wheel	16 Load wheel	16 Steer wheel	6	10		16
559/127-406,4	22 x5 x16	●				1910	1570	1700	1430		1500	1360	24
585/127-406,4			●			1805	1480	1610	1355		1420	1290	27
500/152-406,4		●				2100	1725	1875	1575		1650	1500	24
508/152-406,4	20 x 6 x16	●	●			2160	1775	1930	1620		1695	1545	24
559/152-406,4	22 x 6 x16	●	●			2450	2000	2180	1830		1915	1740	29
508/178-406,4	20 x 7 x16	●	●			2595	2135	2315	1945		2040	1855	30
559/178-406,4	22 x 7 x16	●	●			2975	2450	2650	2230		2335	2125	35
500/180-406,4		●				2550	2100	2275	1910		2005	1820	29
508/203-406,4	20 x 8 x16	●				3010	2470	2690	2260		2365	2150	34
559/203-406,4	22 x 8 x16	●	●			3500	2875	3130	2625		2750	2500	40
500/229-406,4		●				3310	2750	2955	2480		2600	2365	36
508/229-406,4	20 x 9 x16	●				3445	2830	3075	2580		2705	2460	38
559/229-406,4	22 x 9 x16	●	●			4050	3325	3600	3025		3160	2875	45
559/254-406,4	22 x10 x16	●	●			4575	3750	4080	3425		3595	3270	50
559/305-406,4	22 x12 x16	●	●			5625	4625	5030	4225		4420	4025	60
559/356-406,4	22 x14 x16	●				6710	5510	5990	5030		5270	4790	71
559/406-406,4	22 x16 x16	●				7750	6370	6930	5820		6100	5540	82
550/120-410		●				1750	1440	1565	1315		1375	1250	23
610/150-410		●				2505	2055	2235	1880		1965	1790	38
550/160-410		●				2550	2100	2280	1915		2005	1825	28
630/180-410		●				3025	2480	2700	2270		2375	2160	46
645/300-410		●				6060	4960	5275	4330		4485	3935	79
645/350-410		●				7315	5985	6365	5225		5415	4750	94
545/ 90-450		●				1305	1075	1165	980		1025	930	13
570/200-450		●				3350	2755	2990	2510		2630	2395	42
570/240-450		●				4130	3390	3685	3095		3245	2950	51
559/152-451	22 x 6 x17¾		●			2355	1935	2105	1765		1850	1680	25
559/203-451	22 x 8 x17¾		●			3280	2695	2930	2460		2575	2345	34
660/203-480			●			3700	3035	3220	2645		2740	2400	56
660/250-480			●			4780	3925	4160	3415		3540	3105	72
760/250-500		●				5440	4450	4730	3885		4030	3530	92
660/127-508	26 x 5 x20		●			2160	1775	1930	1620		1700	1545	29
650/130-510		●				2210	1820	1975	1655		1735	1580	35
711/178-559	28 x 7 x22	●				3565	2930	3180	2675		2800	2545	49
711/203-559	28 x 8 x22	●				4190	3445	3740	3140		3290	2995	56
711/254-559	28 x10 x22	●	●			5470	4495	4885	4100		4300	3905	69
711/305-559	28 x12 x22	●	●			6760	5545	6035	5070		5310	4830	83
711/356-559	28 x14 x22	●				8030	6595	7170	6020		6310	5735	99
711/406-559	28 x16 x22	●				9280	7620	8290	6960		7300	6630	115
750/120-589		●				2175	1790	1940	1630		1710	1555	36
750/140-589		●				2715	2230	2425	2035		2135	1940	41
750/160-589		●				3245	2665	2900	2435		2550	2320	43
750/200-589		●				3955	3245	3530	2965		3110	2825	61
968/240-670		●				6095	5000	5300	4350		4510	3960	118
900/120-720		●				2440	2000	2180	1830		1915	1745	45
900/200-720		●				4580	3760	4090	3435		3600	3270	75

▲ = Baret-Profil